

## Silt Traps and Filters

Separator installations can be made more effective by the inclusion of a silt trap. These prevent much solid matter entering the separator and reduce the frequency of pump-outs and cleaning.

We have a number of different models (as shown here) and one will be suitable for your particular application.




The **Standard Silt / Debris Trap** with easy lift-out boxes (for easy emptying), twin 4" outlets and is supplied with the **Primary Filter** and a **Squeegee**. Is suitable for modest washpads and particularly where organic matter would be present, (i.e. grass, leaves etc.) *Not suitable for large quantities of mud etc.* Size 600 x 300 x 300 mm.



The **GRP Silt Trap (FST/1)** is the one we sell most of and is ideal for larger vehicle wash areas and where mud etc. is present. Includes a "dipper pipe" outlet to prevent floating matter passing to a separator or other system.

**GRP Silt Trap** for vehicle wash areas (grate not shown)  
Supplied with framed and hinged grates that comply with EN124

Grate codes	B125 GRATE - FST1/B
	C250 GRATE - FST1/C
	D400 GRATE - FST1/D
	E600 GRATE - FST1/E



Size: 1980 mm long x 680 mm wide x 1050 mm deep.

Depending on the loading, we have 4 types of grating: B125 = 12.5 tonnes, C250 = 25 tonnes, D400 = 40 tonnes, E 600 = 60 tonnes. Gratings feature a hinged mount on the long side to facilitate easier opening and silt removal.

The **Large Silt Trap (SPLST)** is built to order and to the size you require. It comes with a heavy duty removable grid to enable easy access for emptying. Ideal for larger areas where greater quantities of mud may be present, especially where heavy plant and equipment is involved.

